



NO.	PART NAME	MATERIAL
1	BODY	SSTL ASTM A351 GR. CF8M
2	SCREEN	
	PERF. DIA. MESH	
3	COVER	SSTL ASTM A351 GR. CF8M
4	YOKE	DUCTILE IRON
5	YOKE SCREW	STEEL
6	O-RING	VITON
7	STUD	STEEL
8	DRAIN PLUG	STAINLESS STEEL
9	BODY PLUG	STAINLESS STEEL

NOTES:

1. INLET/OUTLET 150 LB. RAISED FACED FLANGED CONNECTIONS PER ANSI B16.5.
2. 5/8" DIAMETER SLOTTED FOOT PADS FOR 8" SIZE.
3. DIMENSION "G" (NPT) IS FOR DRAIN PLUG, ITEM 8.
4. ITEM 9, BODY PLUG IS NOT TO BE USED AS DRAIN.
5. MAX. WORKING PRESSURE: 200 PSI @ 100° F (13.8 BAR @ 37.8° C)

CUSTOMER:  
P. O. NO.:  
REG. NO.:  
QUOTE NO.:  
TAG NO.:

PIPE SIZE (NOMINAL)	DIMENSIONS										WEIGHT (DRY) LBS. KGS.	PART NO.					
	A		B		C		D		F				G (NOM.)	H		J	
	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	
8" (200mm)	27.00	/ 686	40.00	/1016	15.50	/394	27.00	/ 686	60	/1524	1/2 (15)	15.75	/400	8.63	/219	550/ 249	ST0720800R2C

<b>FATON</b>	Monarch Asia Pacific Pty Ltd Brisbane, Australia +61 (0) 7 3298 5000 www.monarchindustrial.com.au		
	NAME <b>MODEL 72 SIMPLEX STRAINER 150# RAISED FACE FLANGE SIZE 8" STAINLESS STEEL</b>		
DRAWN FM	DATE 1/25/95	CERT. LF	DATE 1/25/95
SIZE A	DWG NO	<b>SD072030</b>	
			REV C

UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED.

ELECTRONIC FILE NAME: SD072030.DWG  
REF. ECR DE07 DATE 11/1/05